



上海世秀化工有限公司

Shanghai Seashow Chemical Co., Ltd.

paulxuchen@126.com 徐晨 13735586926

产品说明书

SG480 脂肪族中硬性漆革光油

一. 产品说明及用途：

本品为脂肪族阴离子型水性聚氨酯分散液。流平性好。成膜强度高，手感光滑、光亮，耐磨，耐水解，可用于漆革及其它高光皮革的顶层涂饰。

二. 乳液技术指标：

外观： 蓝光半透明乳液

固含量（%）： 30±2

pH 值（1/10）： 7~9

三. 胶膜特性： 硬性

四. 使用方法：配成浆料后喷涂。

五. 包装、运输和贮存：

60kg、120kg 塑料大口桶包装。非危险品，按普通水溶液类物品运输。贮存在室内阴凉处，储存温度 5-35℃，保质期 12 个月。

Product Instruction Booklet

SG480: Aliphatic medium hard lacquer leather varnish.

1. Product description and usage:

This product is aliphatic anionic waterborne polyurethane dispersion. Good leveling property. High film-forming strength, smooth, bright, wear-resistant, hydrolysis resistant, can be used for top coating of lacquer leather and other high gloss leather.

2. Emulsion technology index:

Appearance: blue light translucent emulsion

Solid content (%): 30 ± 2

PH value (1 / 10): 7-9

3. Film properties: hardness

4. Use suggestion: spray after preparing slurry.

5. Packaging, transportation and storage:

60kg, 120kg plastic big mouth barrel packaging. Non dangerous goods shall be transported as ordinary water solution. Store in a cool place indoors at 5-35 °C for 12 months.