



上海世秀化工有限公司
Shanghai Seashow Chemical Co., Ltd.
paulxuchen@126.com 徐晨 13735586926

产品说明书

SX-6345B 水性粘结树脂

一、 特征描述：

1. 本产品为水性粘结树脂。
- 2 树脂成膜软弹，粘结性好，粘结牢度佳。

二、 使用说明：

使用于 PU 革等；适合研磨树脂，粘结层树脂，发泡树脂。

使用前请搅拌均匀，小试；

三、 技术指标：

外观：乳白色液体

成分：脂肪族水性聚氨酯

溶剂：软水

固含量：45±2%

粘度：50-2000CPS/25℃

包装： 180Kg 铁桶包装或根据客户要求包装。

四、 贮藏： 存放于阴凉干燥处，使用后请密封好，避免阳光直射；安全保质期为三个月。

备注：因各厂家生产工艺不同，故此工艺仅作参考。

Product Instruction Booklet

SX-6345B:Waterborne Adhesive Resin

Feature Description:

This product is a waterborne adhesive resin.

The film is soft and elastic, with good adhesion and strong bond solidity property.

Instructions:

It is suitable for PU leather, grinding resin, bonding resin and foaming resin.

Please mix well before use, and make a trail test in priority.

Technical Indicators:

Appearance:	Milky white liquid
Ingredients:	Aliphatic Waterborne Polyurethane
Solvent:	Soft water
Solid content:	45 ± 2%
Viscosity:	50-2000cps / 25 °C

Packaging: 180kg iron drum or according to customer requirements.

Storage: store in a cool and dry place, please seal well after use, avoid direct sunlight; the safe shelf life is three months.

Note: due to different production processes of different manufacturers, specific situation please contact with us directly ,this process is only for common reference.