



上海世秀化工有限公司

Shanghai Seashow Chemical Co., Ltd.

paulxuchen@126.com 徐晨 13735586926

产品说明书

SX-6111水性透亮树脂

一、 特征描述：

1. 本产品由特殊多元醇合成的脂肪族水性聚氨酯。
2. 树脂柔软，丰满度佳，展色性佳。

二、 应用范围：

复合胶水

纤维处理

使用前请搅拌均匀，小试；

三、 技术指标：

外观：透明液体

成分：阴离子脂肪族水性聚氨酯

固含量（%）：33±1

酸碱度：6.5-8.5

包装： 120K 塑料桶包装或根据客户要求包装。

四、 贮藏： 存放于阴凉干燥处，使用后请密封好，避免阳光直射；

安全保质期为三个月。

备注：涂膜性能 5-7 天后达到最高

本品可与其他阴离子或非离子 PU 树脂搭配使用产品用剩后立即密封保存，防止结皮沾灰影响使用。

Product Instruction Booklet

SX-6111 Waterborne Transparent Resin

Feature Description:

1. The product is Aliphatic Waterborne Polyurethane synthesized by special polyols.
2. The resin is soft, with good fullness and good color development.

Application Scope:

Compound glue

Fiber treatment

Please mix well before use, and make a trial test in priority

Technical Indicators:

Appearance Transparent liquid

Ingredients: Anionic Aliphatic Waterborne Polyurethane

Solid content (%) : 33 ± 1

PH: 6.5-8.5

Packing: packed in 120K plastic barrel or according to customer's requirements.

Storage:

Store in a cool and dry place, please seal well after use, avoid direct sunlight;

The safety guarantee period is three months.

Note:

The coating performance reaches the highest after 5-7 days

This product can be used with other anionic or non-ionic PU resin. It can be sealed immediately after use to prevent the use of the product from being affected by dirt on the skin.