



上海世秀化工有限公司

Shanghai Seashow Chemical Co., Ltd.

paulxuchen@126.com 徐晨 13735586926

产品说明书

纸张薄膜用自消光树脂 SX-6411G

1 概述

本产品是由特殊工艺合成的阴离子型自消光脂肪族水性聚氨酯分散体。

具有高触感，手感，绒感，高消光的特性。

2 技术指标：

外观：乳白色液体

固含：35±2

pH (25°C) : 8±2

粘度 (25°C, cps) : 500-2000

分散体类型 阴离子型

3 应用：主要应用于纸张、薄膜触感油，皮革涂饰剂，印花哑面，哑光涂料。

4 主要特性：透度优异，哑度低，流平好，高附着力。

耐白电油，耐酒精性能优异。

抗刮性强。

5 储存性：请在密封状态下置于干燥阴凉避光处，5~35°C，可储存一年以上。

6 包装：120 (kg/桶) ， 20 (kg/桶) ， 塑料桶包装。

Product Instruction Booklet

SX—6411G: Waterborne Matte Resin for Paper & Film

General Introduction:

The product is an anionic self-extinction Aliphatic Waterborne Polyurethane Dispersion synthesized by a special process.

It has the characteristics of super good feeling in hand touch & good velvet performance and high self-extinction advantage.

Technical Indicators:

Appearance:	Milky white liquid
Solid content:	35 ± 2
pH (25°C) :	8 ± 2
Viscosity (25 °C, CPS):	500-2000
Dispersion type:	Anionic type

Application:

Mainly used in paper, film touch oil, leather finishing agent, printing matte, matte coating.

Main characteristics: Excellent transparency, low dullness and good leveling property.

Super good adhesion property.

Excellent resistance to white oil and alcohol.

Strong scratch resistance.

Storage: please put it in a dry, cool and dark place under sealed condition, 5 ~ 35 °C, and it can be stored for more than one year.

Packaging: 120 (kg / barrel), 20 (kg / barrel) plastic barrel.