



上海世秀化工有限公司  
Shanghai Seashow Chemical Co., Ltd.  
[paulxuchen@126.com](mailto:paulxuchen@126.com) 徐晨 13735586926

## 产品说明书

# SF-6740B 水性软弹树脂

### 一、 特征描述：

1. 本产品为水性软弹树脂。
- 2 树脂成膜软弹，粘结性好。

### 二、 使用说明：

使用于 PU 革等；适合研磨树脂，粘结层树脂，发泡树脂。

使用前请搅拌均匀，小试；

### 三、 技术指标：

外观：乳白色液体

成分：脂肪族水性聚氨酯

溶剂：软水

固含量：40±2%

粘度：50-2000CPS/25℃

包装： 180Kg 铁桶包装或根据客户要求包装。

### 四、 贮藏： 存放于阴凉干燥处，使用后请密封好，避免阳光直射；安全保质期为三个月。

备注：因各厂家生产工艺不同，故此工艺仅作参考。

# Product Instruction Booklet

## SF-6740B: Water Based Soft Elastic Resin

### Feature Description:

The product is water-based soft elastic resin.  
The resin is flexible with good adhesion property.

### Instructions:

It is suitable for PU leather, grinding resin, bonding resin and foaming resin.  
Please mix well before use, and make a trail test in priority;

### Technical Indicators:

Appearance:	Milky white liquid
Ingredients:	Aliphatic Waterborne Polyurethane
Solvent:	Soft water
Solid content:	40 ± 2%
Viscosity:	50-2000cps / 25 °C

**Packaging:** 180kg iron drum or according to customer requirements.

**Storage:** store in a cool and dry place, please seal well after use, avoid direct sunlight; the safe shelf life is three months.

**Note:** this process is only for common reference for specific case welcome to contact with us directly for detail discussion.